

FIBRANgyps JF 60



Product Description

Joint filler in powder to be mixed with water for manual application, short setting time.
3B CE marked according to UNI EN 13963.

Applications

Bedding compound and finishing, suitable as a first-and second-hand.

Features	U. M.	Value	Standard
Reaction to fire	Class	A1	EN 13501-1
Weight	kg/m ³	825 ± 25	-
Density dried product	kg/m ³	1050 ± 50	-
Workable time	min	60	EN 13963
Setting time	min	180	EN 13963
Performance	kg/m ³	0,39	-
Preparation	-	Manual mixing with clean tools	-
Rating water/powder	-	60/40	-

Storage and Application

Store in a cool, dry, ventilated and protected area. Use within 12 months from the date of production. Do not use at temperatures below + 5 ° C and above + 35 ° C.

FIBRAN reserves the right to alter or amend product specifications without notice. The information included in this publication is correct to the best of our knowledge at the time of printing. Whilst FIBRAN will endeavor to ensure publications are up to date, it is the user's responsibility to check with the company the validity of the information prior to materials' use. For more information visit the web site www.fibran.it.

Date 31/07/2018

FIBRAN S.p.A. via Fiasella 5/11 16121 GENOVA Italy - ph. +39 010 25466.1 fax +39 010 25466.949 - www.fibran.it - tech@fibran.it